

## Electric crimping presses

**SERIE CP**

20

40 E

80

CP series electric presses for banded terminals



## FEATURES

- CP series crimping presses equipped with safety protection, steel body and English language display
- The terminal reel holder is adjustable
- Adjustable crimping height with precision of about 0,03 mm
- Equipped with a mini working-lamp, LED with cool light and low energy consumption.

## OPTIONS


- CFM system (Crimp Force Monitoring). CFM stops the machine in case of anomaly, but with no elimination of the defective part

## TECHNICAL SPECIFICATIONS

	CP 20	CP 40 E	CP 80
Crimping height	135,78 mm		
Crimping force	20 kN	40 kN	80 kN
Stroke	40 mm		
Speed	160 s.p.m.	160 s.p.m.	80 s.p.m.
Power	750 W	1500 W	3000 W
Power supply	220 VAC / 5 Hz	220 VAC / 5 Hz	380 VAC / 50 Hz
Dimensions	325 x 280 x 730 mm	360 x 300 x 890 mm	430 x 360 x 1030 mm
Weight	75 Kg	105 Kg	200 Kg

**CE Conformity:** CP series crimping presses fully compliant with CE regulations and EMC equipment guidelines for mechanical, electrical and electromagnetic compatibility.

**Note:** we recommend to send samples with the application requirements for a preliminary examination.



Working Lamp



Adjustable crimping height



Terminal guide



Terminal reel holder