



EcoStrip 9380

Welcome to the Future of Entry Level Cut & Strip

- Three in one transport unit
- Improved price to performance ratio
- Simple machine operation thanks to Schleuniger's standardized S.ON user interface
- The latest technology, cleverly combined with Schleuniger's industry renowned precision

CUT & STRIP

EcoStrip 9380



Simply Capable

Transforming your expectations: Get a machine with flexible, «all in one» roller-, belt- and short mode transport drives.

Cut your cost, strip your efforts: The machine is economically priced, yet in terms of performance, it exceeds previous models by 20 percent.

Explore simplicity: Simple machine operation thanks to Schleuniger's standardized S.ON user interface with 5.7" color touchscreen.

Precision has a name: All driven axes are powered by our proven *Bricks* electronic platform.



The EcoStrip 9380 capabilities are significantly expanded due to quick change transport unit for rollers, belts and short mode processing. With the belt drive you benefit of three configurations: 1. Belt drive, 2. Short mode, 3. Roller drive (butterfly – roller with belt).

Compatible with a wide range of accessories (prefeeder, marking, stacking, coiling and tying) for future expansion.

Minimize training and setup time with S.On software. Cayman and S.WOP compatible for integration into various networks.

| Technical Specifications | |
|-----------------------------------|---|
| Max. cable outer diameter | 8.0 mm (0.31") |
| Max. cable cross section standard | 0.05 – 8 mm ² (10mm ² EN60228 class 5&6) AWG 8 |
| Blade sets usable up to x mm | 1 x 12 mm (1 x 0.47") |
| Feeding system | Rollers or Belts |
| Single conductor (1 step) | Yes |
| Multilayer | Yes |
| Max wire or cable length | 1'000'000 mm (39.370") |
| Pull off length left side | 46 mm (1.18") |
| Pull off length right side | 152 mm (5.98") |
| Short mode up to | 46 mm (18 mm measured on remaining insulation length) |
| Interfaces | Standard: Ethernet for PC, USB Optional: SMI (I/O's), Prefeeder, Wire marker (HS), Inkjet printing, Stacker / Coiler |
| Power Supply | 100-240 VAC |
| Dimensions (L x W x H) | 435 x 397 x 360 mm (17.1 x 15.6 x 14.2 ") |
| Weight | 25 kg (55.1 lbs.) |