

Low pressure overmolding unit

HI 20 H

Low pressure horizontal injection overmolding unit for Hot Melt materials. Dual working station



mecatronicitalia.com

MECATRONIC

SOLUTIONS & SERVICE

FEATURES

- 2 x four column press
- Dual working station
- Separate processing parameters for the two stations
- 2 x 5 I melting tank
- Electronic injection pressure adjustment from 0,5 to 50 bar (EPR)
- Mold clamping force 5 T
- Weekly switch-on time programming
- Air over oil cylinder for a bigger clamping force
- 6 indipendent PID temperature control zones
- Pneumatic ejection system on both station
- Cycle start with dual palm button and light curtain
- Temperature limits with programmable alarms
- Quick mold replacement

OPTIONS

- Mold clamping force 10 T
- Chiller CBV 5.1, cooling mold unit with adjustable temperature
- 2 x 10 | Melting tank / 2 x 7 | Melting tank / 2 x 15 | Melting tank
- □ Automatic Feeding System (AFS)
- D 10 Resin Dryer
- □ Network interface (Industry 4.0)

TECHNICAL SPECIFICATIONS

	HI 20 H
Mold clamping force	5 T (optional 10 T)
Tank capacity	2 x 5 l (optional 2 x 10 l / 2 x 15 l / 2 x 7 l)
Temperature control zones	6
Max. tank and gun temperature	250° C
Gun	Standard nozzle cone 36.4° Optional nozzle cone 90°
Mold stroke	150 mm
Clamping system	Air over oil cylinder
Control system	Touch screen 7" HMI and PLC
Safety protection	Light curtain and two hands control for cycle start
Air supply	6 bar, 0.18m³/cycle
Power supply	380 VAC 3+N+T 50/60 Hz 32 A
Dimensions and Weight	1300 x 950 x 1865 mm / 610 kg
Working plate height	H: 1000 mm + mold height

CE Conformity: HI 20 H is fully compliant with CE regulations and EMC equipment guidelines for mechanical, electrical and electromagnetic compatibility.

Note: we recommend to send samples with the application requirements for a preliminary examination.


The unit works with Technomelt, Thermelt and Macromelt resins and Hot Melt polyamide and polyolefin resins.

mecatronicitalia.com






MOLD DIMENSIONS



FROM 120 mm TO 200 mm



V. 06/2022